






# C SERIES

C100

C120

MODEL	C100	C120
CUTTING WIDTH (mm)	970	1170
RECOMMENDED EXCAVATOR (ton)	4-6.5	5-8
WEIGHT (Kg)	280	325
OIL PRESSURE (bar)	230	230
OIL FLOW (l/min)	40-80	40-80
NUMBER OF KNIVES	36	48
NUMBER OF HAMMERS	12	16
MAX CUTTING DIAMETER (mm)	60	60
A DIMENSION (mm)	785	785
B DIMENSION (mm)	1135	1335
C DIMENSION (mm)	500	500
SELF-LEVELLING SUPPORT WEIGHT (Kg)	31	31
EXCAVATOR ATTACHMENT WEIGHT (min-max Kg)	15-40	15-40



Fluidbox for complete and safe engine management, with maximum shockproof valve, anti-cavitation system and flow regulation to set the rotor speed correctly.



Predisposition of holes on the upper part of the machine, which allows to position customized attachment on 6 different positions (C100) or 8 different positions (C120).



Replaceable wear-resistant skids.



Double-bottomed case to increase robustness and optimize the cutting volume.



Standard with 2mt hydraulic hoses. Available as **optional**: set of hoses with customized lengths.



Available as **optional**: standard attachment and pins with customized measurements, flat plate for attachment as standard.