

SORTING GRAPPLE

(PF version available: without rotation system)

P10 - P15 - P20 - P25 - P30 - P40

SORTING GRAPPLE

Sorting grapple with bidirectional hydraulic rotation as standard. P10 model has a rotating joint, while P15-P20-P25-P30-P44 models have a hydraulic rotation with slewing ring. They are made up of a high resistance frame. The grapple can be set up with side doors to increase its loading capacity.



MODEL	P10	P15	P20	P25	P30	P40
MACHINES (TON)	1,5>3,0	3>5	4>8	6>10	11>14	14,1>15
ROTATION ANGLE	360°	360°	360°	360°	360°	360°
WEIGHT (Kg)	120	260	330	410	700	800
MAX CAPACITY (Lt.)	50	70	90	120	160	250
A DIMENSION (mm)	820	1100	1430	1430	1870	1870
B DIMENSION (mm)	340	420	500	650	660	900
C DIMENSION (mm)	280	450	480	480	620	620
FULCRUM DISTANCE (D)	310	380	560	560	710	710
HEIGHT (E)	720	850	1010	1010	1210	1210
MAX PRESSURE CYLINDER (Bar)	220	250	250	250	250	250
CYLINDER FLOW RATE (L/min)	9	20	24	24	30	32
MAX ENGINE PRESSURE (Bar)	180	200	200	200	200	200
ENGINE FLOW RATE (L/min)	20	6	6	6	5	5