



A = 2220 mm

B = 1315 mm

C = 1340 mm

RMU40

AIR FILTER	High Capacity Cartridge. Cyclone Prefilters.
ELECTRICAL SYSTEM	12V CC
FUEL TANK	35 L
MAXIMUM SPEED	1st gear 4.5 km / h - 2nd gear 9 km / h
MAX SLOPE	55°
OPERATING WEIGHT	1750 Kg

ENGINE

MODEL	Yanmar 3TNV86CT
DISPLACEMENT / N ° CYLINDERS	1.568cc/3
MAX POWER	40 hp/30 kW
EMISSIONS	Eu Stage V
BIODEGRADABLE MOTOR OIL	Optional
COOLING FAN	Reversible-Manual/Automatic

HYDRAULIC SYSTEM

TYPE	Closed-Loop
MAX PRESSURE ON PTO	320 Bar
MAX FLOW ON PTO	55 l/min
TANK CAPACITY	32 l
BIODEGRADABLE HYDRAULIC OIL	Optional

FRAME

TYPE OF FRAME	Variable track
---------------	----------------

REMOTE CONTROL

BRAND	Imet
WORKING FREQUENCY	433.050-434.790 MHz e 2,4 GHz
RANGE OF ACTION	100 m
JOYSTICK	Proportional
BATTERY	Dual rechargeable lithium battery
BATTERY CHARGER	On board
INCLUDED AS STANDARD	3 batteries
DISPLAY	4,3" colour display

